

**Präzisionsstahlrohre EN 10305-2 (DIN 2393)**

gezogen, geschweißt

<b>Wandstärke</b>										
<b>Außen- durchmesser</b>	<b>1</b>	<b>1,5</b>	<b>2</b>	<b>2,5</b>	<b>3</b>	<b>3,5</b>	<b>4</b>	<b>4,5</b>	<b>5</b>	<b>6</b>
<b>12</b>	0,271	0,388	0,493							
<b>13</b>	0,296	0,425	0,543							
<b>14</b>		0,462	0,592	0,709						
<b>15</b>	0,345	0,499	0,641	0,771						
<b>16</b>	0,370	0,536	0,691	0,832	0,962					
<b>18</b>	0,419	0,610	0,789	0,956	1,110	1,252				
<b>20</b>	0,469	0,684	0,888	1,079	1,258	1,424	1,578	1,720		
<b>22</b>	0,518	0,758	0,986	1,202	1,406		1,777			
<b>24</b>			1,085	1,326	1,554		1,973			
<b>25</b>	0,592	0,869	1,134	1,387	1,628	1,856	2,072		2,466	
<b>26</b>	0,617	0,906	1,184	1,449						
<b>28</b>	0,666	0,980	1,282	1,572	1,850	2,115	2,368		2,836	
<b>30</b>	0,715		1,381	1,695	1,998		2,565	2,830	3,083	
<b>32</b>	0,764		1,480	1,819	2,146	2,460	2,762		3,329	
<b>34</b>	0,814	1,202	1,578	1,942	2,294	2,633				
<b>35</b>	0,838	1,239	1,628	2,004	2,367		3,058		3,699	
<b>36</b>			1,677	2,065	2,441					
<b>38</b>		1,350	1,776	2,189	2,589		3,354		4,069	4,735
<b>40</b>	0,962	1,424	1,874	2,312	2,737		3,551		4,316	5,031
<b>42</b>	1,011			2,435	2,885					
<b>45</b>		1,609	2,121	2,620	3,107		4,044		4,932	5,771
<b>48</b>			2,269		3,329		4,340		5,302	
<b>50</b>	1,794		2,368		3,477			5,049	5,549	6,511
<b>55</b>		1,979	2,614		3,847		5,031		6,165	
<b>60</b>		2,164	2,861		4,217		5,524		6,782	7,990
<b>65</b>			3,853		4,587			6,714	7,398	
<b>70</b>			3,354		4,957		6,511		8,015	
<b>75</b>			3,601						8,631	
<b>80</b>			3,847		5,697		7,497		9,248	10,950
<b>85</b>			4,094		6,067				9,865	11,690
<b>90</b>			4,340				8,484		10,481	
<b>95</b>									11,098	
<b>100</b>									11,714	13,909
<b>110</b>									12,947	
<b>120</b>			5,821		8,656		11,443		14,180	16,868
<b>160</b>									19,112	

Nicht aufgeführte Abmessungen auf Anfrage.